

Technical Specifications Confidence C2

Sensitivity (2.83 V/1 m):	87 dB
IEC Long Term Power Handling:	170 watts
Impedance, Nominal:	4 ohms
Frequency Response: (+/- 3 dB)	28 Hz – 25 kHz
Internal Cabinet Volume:	43 litres
Bass Principle:	Bass reflex
Weight:	40 kg
Dimensions (W x H x D):	238/420 x 1550 x 445 mm
Crossover:	2 (3) way
Crossover Frequencies:	2200 (8000) Hz
Crossover Slope:	Woofer 6 dB/octave; Tweeter 6 dB/octave
Recommended Placing:	Floor free standing

Remarks:	Tweeter:	<ul style="list-style-type: none">• 28 mm soft dome• Esotar²• Magnetic fluid• 10 mm machined aluminium front, with high heat-dissipation, integrated in baffle• Pure aluminium wire voice coil• Integrated metal rear chamber, with built in acoustic-vent• Large neodymium magnet rings
	Woofers:	<ul style="list-style-type: none">• 17 cm MSP cone• 75 mm pure aluminium wire voice coil
	Crossover:	<ul style="list-style-type: none">• Thick glass fibre reinforced PCB with extra copper thickness• Capacitors with low loss dielectricum• Zero compression resistors• The crossover is impedance corrected