

Technical Specifications Confidence Center

Sensitivity (2.83 V/1 m):	87 dB
IEC Long Term Power Handling:	> 300 watts
Impedance, Nominal:	4 ohms
Frequency Response: (+/- 3 dB)	45 Hz – 22 kHz
Internal Cabinet Volume:	25 litres
Bass Principle:	Bass reflex
Weight:	20.6 kg
Dimensions (W x H x D):	80 x 270 / 300 x 380 mm
Crossover:	2 (3) way
Crossover Frequencies:	2200 (6000) Hz
Crossover Slope:	Woofer 6 dB/octave; Tweeters 6 dB/octave
Recommended Placing:	Above or below screen

Remarks:	Speaker:	<ul style="list-style-type: none"> • Center speaker with adjustable tilt for placement high or low • Switch for optimal dispersion characteristic placed high or low
	Tweeters:	<ul style="list-style-type: none"> • 28 mm soft dome • Esotar² • Magnetic fluid • 10 mm machined aluminium front, with high heat-dissipation, integrated in baffle • Pure aluminium wire voice coil • Integrated metal rear chamber, with built in acoustic-vent • Large neodymium magnet ring • Shielding magnet
	Woofers:	<ul style="list-style-type: none"> • 17 cm polypropylene cone • 75 mm pure aluminium wire voice coil
	Crossover:	<ul style="list-style-type: none"> • Thick glass fibre reinforced PCB with extra copper thickness • Capacitors with low loss dielectricum • Zero compression resistors • The crossover is impedance corrected