

Technical Specifications Contour S 3.4

Sensitivity (2.83 V/1 m):	86 dB
IEC Long Term Power Handling:	< 270 watts
Impedance, Nominal:	4 ohms
Frequency Response: (+/- 3 dB)	35 Hz – 25 kHz
Internal Cabinet Volume:	44 litres
Bass Principle:	Bass reflex
Weight:	33.3 kg
Dimensions (W x H x D):	357 x 1226 x 366 mm
Crossover:	2 way
Crossover Frequencies:	2000 Hz
Crossover Slope:	Woofer 6 dB/octave; Tweeters 6 dB/octave
Recommended Placing:	Floor, freestanding

Remarks:	Tweeters:	<ul style="list-style-type: none">• 28 mm soft dome – technology from Esotar²• Magnetic fluid• 5 mm machined aluminium front, with high heat-dissipation, integrated in baffle• Pure aluminium wire voice coil
	Woofers:	<ul style="list-style-type: none">• Die-cast chassis• 17 cm one-piece moulded MSP polypropylene cone• 75 mm long throw pure aluminium wire voice coil, wound on Kapton® former
	Crossover:	<ul style="list-style-type: none">• Thick glass fibre reinforced PCB with extra copper thickness• Capacitors with low loss dielectricum• Zero compression resistors• Inductors wounded on “air cores”• The crossover is impedance corrected