

Technical Specifications Contour S C

Sensitivity (2.83 V/1 m):	86 dB
IEC Long Term Power Handling:	150 watts
Impedance, Nominal:	4 ohms
Frequency Response: (+/- 3 dB)	65 Hz – 25 kHz
Internal Cabinet Volume:	25 litres
Bass Principle:	Bass reflex
Weight:	10.3 kg
Dimensions (W x H x D):	490 x 160 x 303 mm
Crossover:	2 way
Crossover Frequencies:	1400 Hz
Crossover Slope:	6 dB/octave
Recommended Placing:	Stand or shelf

Remarks:	Speaker:	<ul style="list-style-type: none">• Centre speaker
	Tweeter:	<ul style="list-style-type: none">• 28 mm soft dome• Esotar• Magnetic fluid• Pure aluminium wire voice coil
	Woofers:	<ul style="list-style-type: none">• Die-cast chassis• 15 cm one-piece moulded MSP polypropylene cone• 75 mm long throw pure aluminium wire voice coil, wound on aluminium former
	Crossover:	<ul style="list-style-type: none">• Thick glass fibre reinforced PCB with increased copper thickness• Capacitors with low loss dielectric for clearer sound• Zero compression resistors for dynamic reproduction• Inductors wound on "air cores"• Impedance corrected crossover for ideal Amplifier interface