

Technical Specifications Evidence Temptation

Sensitivity (2.83 V/1 m):	90 dB
IEC Long Term Power Handling:	500 watts
Impedance, Nominal:	4 ohms
Frequency Response: (+/- 3 dB)	29 Hz – 25 kHz
Internal Cabinet Volume:	64 litres
Bass Principle:	Bass reflex
Weight:	113 kg
Dimensions (W x H x D):	210 / 390 x 1933 x 490 mm
Crossover:	3 (5) way
Crossover Frequencies:	(300 Hz), 500 Hz, 2300 (8000) Hz
Crossover Slope:	Woofers 6 dB/octave; Midranges 6 dB/octave; Tweeters 6 dB/octave
Recommended Placing:	Floor free standing

Remarks:	Tweeters:	<ul style="list-style-type: none"> • 28 mm soft dome • Magnetic fluid • 40 mm aluminium-alloy front, with high heat-dissipation, integrated in baffle • Pure aluminium wire voice coil • Aluminium-alloy rear chamber with high heat dissipation • Very large neodymium magnet rings
	Midranges:	<ul style="list-style-type: none"> • 15 cm one-piece moulded MSP cone • 38 mm pure aluminium wire voice coil
	Woofers:	<ul style="list-style-type: none"> • 17 cm one-piece moulded MSP cone • 75 mm long throw pure aluminium wire voice coil
	Crossover:	<ul style="list-style-type: none"> • Exchangeable filter module • Separate ventilated chamber for filter module • Non-magnetic filter frame • Double thickness glass fibre reinforced PCB with extra copper thickness • All speaker units and the crossover are impedance corrected • Only air-core coils • Capacitors with low loss dielectricum • Zero compression resistors