

## Technical Specifications Excite X36

|                                |  |
|--------------------------------|--|
| Sensitivity (2.83 V/1 m):      | 89 dB  |
| IEC Long Term Power Handling:  | > 250 watts  |
| Impedance, Nominal:            | 4 ohms   |
| Frequency Response: (+/- 3 dB) | 35 Hz – 23 kHz   |
| Internal Cabinet Volume:       | 42 litres  |
| Bass Principle:                | Bass reflex  |
| Weight:                        | 23.5 kg  |
| Dimensions (W x H x D):        | 205 x 1040 x 310 mm  |
| Crossover:                     | 3 way  |
| Crossover Frequencies:         | 500/2000 Hz  |
| Crossover Slope:               | Woofer 6 - 12 dB/octave; Midrange 12 dB/octave; Tweeter 12 dB/octave |
| Recommended Placing:           | Floor  |

|          |          |  |
|----------|----------|--|
| Remarks: | Tweeter: | <ul style="list-style-type: none"><li>• 27 mm soft dome</li><li>• Magnetic fluid</li><li>• Pure aluminium wire voice coil</li><li>• Rear chamber</li></ul>                           |
|          | Woofers: | <ul style="list-style-type: none"><li>• 18 cm with die cast Aluminium chassis</li><li>• MSP cones</li><li>• 38 mm pure aluminium wire voice coil wound on aluminium former</li></ul> |