

Technical Specifications Focus 360

Sensitivity (2.83 V/1 m):	88 dB
IEC Long Term Power Handling:	> 300 watts
Impedance, Nominal:	4 ohms
Frequency Response: (+/- 3 dB)	31 Hz – 25 kHz
Internal Cabinet Volume:	63 litres
Bass Principle:	Bass reflex
Weight:	36.1 kg
Dimensions (W x H x D):	248 x 1240 x 385 mm
Crossover:	3 way
Crossover Frequencies:	400, 2200 Hz
Crossover Slope:	Woofers 12 dB/octave; Midrange 12 dB/octave; Tweeter 12 dB/octave
Recommended Placing:	Floor free standing

Remarks:	Tweeter:	<ul style="list-style-type: none">• 28 mm soft dome• Magnetic fluid• 4 mm aluminium front with high heat-dissipation• Pure aluminium wire voice coil• Integrated metal rear chamber, with integrated acoustic-vent• Large neodymium magnet
	Midrange:	<ul style="list-style-type: none">• 15 cm one piece moulded MSP cone• 38 mm pure aluminium wire voice coil• Die cast aluminium frame
	Woofers:	<ul style="list-style-type: none">• 20 cm one piece moulded MSP cone• 75 mm pure aluminium wire voice coil• Kapton former• Large neodymium magnet• Die cast aluminium frame
	Crossover:	<ul style="list-style-type: none">• The Crossover is impedance corrected• Thick glass fibre-reinforced PCB with extra copper thickness• Capacitors with low loss dielectricum• Zero compression resistors