

# SUB 250<sup>mc</sup>

## Features:

- Active Subwoofer with multimedia compatibility
- 24 cm woofer with 100 mm pure aluminium voice coil
- Integrated 140 watts amplifier
- Automatic Standby/Power
- Selectable (Master/Slave) for standalone or multiple subwoofer configurations
- Adjustable lowpass filter (50 Hz – 150 Hz)
- Adjustable phase (0° / 180°)
- Satellite output with selectable high pass filter (flat / 60 Hz / 80 Hz)

## Technical data:

System:	Active, sealed box
Frequency range (+/- 3 dB):	29 Hz – 250 Hz (+/- 3 dB)
Amplifier power:	140 watts, 4 Ohm
Sub I/O, LFE/slave in:	RCA
Sat/Sub input:	Right/Left unfiltered, RCA
Sub I/O, LFE/to Slave:	RCA
Sat output:	Right/Left, high pass filtered, RCA
Operation mode:	LFE, slave (controls for phase and gain are disabled in slave-mode)
Phase configuration:	0°, 180°
Sat high pass:	Flat, 60 Hz, 80 Hz
Sub low pass:	50 Hz – 150 Hz
Auto turn on (LED = green):	Immediately once signal is detected
Auto turn off (LED = red):	After 15 – 20 minutes without detectable signal
Power consumption	14 watts / 325 watts max.
Cone:	240 mm (10 inch), one piece MSP (magnesium silicate polymer) diaphragm
Coil:	100 mm (4.2 inch), pure aluminium voice coil
Weight:	10 kg
Dimension (W x H x D):	28,9 x 29,4 x 31,8 cm 11.4 x 10.2 x 9.3 inch

## Availability:

March 2007

## Package contents:

1 x Dynaudio Sub 250MC, 1 x owners manual, 1 x power cord, 1 x grille